



applicArt

TECHNICAL INFORMATION

METALLIQUE RANGE

FEATURES

Métallique, replaces traditional solvent-based metal glazes, improving the decorative effect making it more durable as the surface obtained does not darken due to oxidation over time.

All MÉTALLIQUE colours can be used pure or mixed to obtain infinite intermediate and special colours highly appreciated in the field of fine arts and decoration.

The shades of MÉTALLIQUE have excellent resistance on the outside.

APPLICATION

MÉTALLIQUE can be applied with a brush, roller or airbrush, in the delivered condition or diluted with 5 - 10% of water on a wide range of materials such as glass, wood, plastic, paper, fibres, cement plaster, polystyrene, expanded wood, passivated iron with anti-rust.

MÉTALLIQUE, mixed in a measure of not less than 50% in LA VELATURA, LA VELATURA NEUTRA or LA VELATURA LUCIDA, allows to obtain particularly Métallique effects on the wall with the application by brush, sponge, glove, roller, etc.

PERFORMANCE

5-6 m² with 1 litre in two coats, according to the absorption or the nature of the substrate.

DRYING

30 minutes dust free; 1-2 hours in depth.

PLASTIC PACKAGE

1250ml

AVERAGE SPECIFIC WEIGHT

Approximately 1,100 at 20 ° C